

Head #: ME515	Bore Adapter Diameter: 4.25 "
Customer: Pinkowsky	Int Port Adapter: Radiused Inlet
Operator: Boberoo	Exh Port Adapter: None (no adapter)

Test Comments:

Head# ME515 (B!BA)

Valve size style:2.08/1.60

Customer: Tom Pinkowski/Jason Vizenor

Report of:	Test Time		Tested at	Corr to	# Vlvs	Vlv Dia	Stem Dia	Port Area
Comparing	8:47 am		Int: 28"	28.0"	2	2.08"	.341"	1.56 sq in
1 Cylinders	03/29/2012		Exh: 28"	28.0"	2	1.600"	.341"	1.80 sq in
Port	Lift	L/D	Avg CFM	Cyl 1 CFM				

Intake	.050	.024	34.0	34.0
Intake	.100	.048	65.7	65.7
Intake	.150	.072	94.8	94.8
Intake	.200	.096	123.0	123.0
Intake	.250	.120	149.8	149.8
Intake	.300	.144	175.8	175.8
Intake	.350	.168	201.3	201.3
Intake	.400	.192	226.8	226.8
Intake	.450	.216	250.1	250.1
Intake	.500	.240	268.9	268.9
Intake	.550	.264	287.7	287.7
Intake	.600	.288	296.3	296.3
Intake	.650	.313	287.0	287.0
Intake	.700	.337	283.8	283.8
Intake	.750	.361	281.1	281.1
Int Avg	.400	.192	201.7	201.7

Exhaust	.050	.031	38.3	38.3
Exhaust	.100	.063	63.8	63.8
Exhaust	.150	.094	90.3	90.3
Exhaust	.200	.125	116.8	116.8
Exhaust	.250	.156	136.0	136.0
Exhaust	.300	.188	154.3	154.3
Exhaust	.350	.219	171.9	171.9
Exhaust	.400	.250	186.0	186.0
Exhaust	.450	.281	195.2	195.2
Exhaust	.500	.313	201.0	201.0
Exhaust	.550	.344	205.1	205.1
Exhaust	.600	.375	208.6	208.6
Exhaust	.650	.406	210.2	210.2
Exhaust	.700	.438	211.7	211.7
Exhaust	.750	.469	213.0	213.0
Exh Avg	.400	.235	150.1	150.1

